QUESTIONS? IDEAS? SUGGESTIONS?

CONTACT US – THE FKB-TEAM WILL BE GLAD TO ADVISE YOU

Our RSB® Team will be glad to advise you:

Tel. +49 7423 9298-0

Fax +49 7423 9298-55

fkb@fkb-gmbh.com www.fkb-gmbh.com







Wehrstraße 15 / 27 DE 78727 Oberndorf a.N.



PROTECTION

FOR MAN & TECHNOLOGY

FOR IMPROVED SAVETY!

the new 'fire retardant protection wrap' is a conductive thermoplastic compound - the ideal solution wherever reliable fire-resistance is required .

our protective wrapping is made to

protect hydraulic and pneumatic
hoses against shocks, abrasion
and deteriorations.

our protective wrapping can easily be
mounted on existing or new assembled
hydraulic hoses, giving them protection
against wear and damage caused by
aggressive working conditions.

EN 45545-2

HIGHLY TOPICAL

TECHNICAL DETAILS

fire retarding material

temperature range: -20C° - +120C°

colouring: RAL 7012

neets the requirements

UL94/VO

tested and certified acc. to

EN 45545-2

available sizes*:

outsideØ insideØ wall helix wic

12.5 mm 16 mm 1.75 mm 12 mm

m 20 mm 2 mm 14,5 mm

mm 25 mm 2 mm 21 mm

* Nominal dimensions only !