

// 08 LUMOLED SE

TRADITION & MODERNITY

LumoLED SE

There it is – our LumoLED SE lamp. All alone – without any further members of a possible product family.


But do you know what? The LumoLED SE does not need any „companions“ – it can assert itself – it is after all a sensational product which skilfully blends traditional design and state-of-the-art technology.


Protective tube made of borosilicate glass, classical diameter of 70 mm and an efficient LED luminaire inside – that is the LumoLED SE!

The operation of the lamp no longer requires a ballast – neither internally nor externally. The LED luminaire can be operated directly. Convenient!

The modern LED luminaire is replaceable which makes the LumoLED SE low-maintenance and thus service-friendly.

In addition, we offer a good luminous flux, an excellent performance factor, high-quality processing and, under normal conditions, an expected service life of about 50,000 h – that's how a machine lamp should be!





LumoLED SE

// TECHNICAL DATA

ITEM NO.: 591-111-024

Operating voltage	230 V AC 50 Hz
Rated output	16 W
Ambient temp.	-5°C - max. 40°C
System of protection	IP67
Protection class	SK I
Weight	4,67 kg
Protective tube	Borosilicate
Type of lighting	Tubular lamp
Scope of application	Industrial sector



// LIGHT SOURCES

Lifetime	50.000 h
Colour rendering	Ra = 83
Energys efficiency class	A ++
Luminous flux	2500 lm
Light efficiency	156 lm / W
Light colour	4000 K

// ELECTRICAL CONNECTION

Cable gland	M16 x 1,5 Ms nickel-plated
Internal connection	luster terminal, 3-pole
Internal electrical lines	Multinorm wires


// FEATURES

- Robust borosilicate protective tube
- No converter required
- Common M16 cable gland – quick & easy
- Very good price-performance ratio
- Classical diameter of 70 mm

// SHORT OVERVIEW

TYPE	ITEM NO.	VOLTAGE	POWER	LUMINOUS/ LUMEN	PROTECTIVE TUBE	DIMENSIONS/ MM	CONNECTION
LumoLED SE	591-111-024	230 V AC	16 W	2500	Borosilicate	Ø70x1369	cable gland

// TECHNICAL DRAWING



// FIXING (optional)

Fixing clamps



ITEM NO. 599-001-001
Fixing clamp Ø70 mm, galvanised,
straighth



ITEM NO. 599-001-002
Fixing clamp Ø70 mm, galvanised,
angle plug, wall clearance 70 mm,
with distance bush



ITEM NO. 599-001-003
Fixing clamp Ø70 mm, galvanised,
angle plug, wall clearance 100 mm



ITEM NO. 599-001-004
Fixing clamp Ø70 mm, galvanised,
straight, with distance tube



ITEM NO. 599-001-016
Tension clamp D70 mm VPE 1 pc



ITEM NO. 599-001-022
Fixing clamp Ø70 mm,
Stainless steel A4, angle plug,
wall clearance 70 mm

// STANDARDS

EN 55015:2016-04
EN 60598-1:2015-10
EN 62031:2015-09
EN 61000-4-4:2013-4
EN 61000-3-2:2015-3
EN 61000-4-5:2015-03

TECHMALUX